INSTITUT DE FORMATION INTERNATIONALE AUX TRANSPORTS
INSTITUTE FOR INTERNATIONAL TRAINING IN TRANSPORT
INSTITUTO DE FORMACIÓN INTERNACIONAL DE TRANSPORTE

RAILWAYS AND RAILWAY TRANSPORT

Railway Substructure

THE TRACK

in collaboration with
TRANSURB CONSULT

K. DEMEERSEMAN
Engineer at the S.N.C.B.

LAYOUT OF THE TRACK

Table of contents

1. Dynamic characteristics linked to the layout

1.1. Generalities on the line layout
1.2. Centrifugal force
1.3. Lateral acceleration
1.3.1. Definition
1.3.2. Influence of the lateral acceleration
1.4. Maximum admissible lateral acceleration
1.4.1. Comfort and wear limit
1.4.2. Turn-over limit
1.4.3. Lateral shift limit of the loaded track
1.4.4. Derailment limit
1.4.5. Conclusion
1.5. The jerk

2. The cant or the superelevation

2.1. Realisation of the cant
2.2. Theoretical cant
2.3. Minimum cant and cant deficiency
2.4. Maximum admissible cant
2.5. Influence of a mixed traffic on the value of the cant
2.6. Minimum radius of curve for a mixed traffic
2.7. Minimum radius for circulation
2.8. Special cases
2.9. Table of minimum radius as a function of the speed

3. Superelevation ramp

3.1. Realisation of the ramp
3.2. Ramp gradient - twist
3.3. The greatest admissible ramp gradient
3.4. The vehicle moving in a superelevation ramp
3.5. Length of the superelevation ramp
3.6. Need of transition curves

4. Transition curves

4.1. Generalities
4.2. Transition curves for straight ramp of cant
4.3. Variation of cant deficiency in a transition curve
4.4. Length of transition curve
4.4.1. Determination of length
4.4.2. Comment upon the choice of length of transition curve
4.5. Sinusoïdal transition curves

5. Compound and reverse curves

5.1. With transition curves
5.2. Without transition curves
5.2.1. Main lines
5.2.2. Secondary lines

6. Compound curves with different radii

7. Change in gradient

7.1. Value of the radii
7.2. Special cases
7.3. Example

8. Implantation of the layout and longitudinal profile