

# ELECTRIC RAILWAY ENGINEERING

*by*

T. FERGUSON

A.M.I.E.E.

*Formerly Chief Engineer, Traction Projects Dept.,  
Metropolitan-Vickers Electrical Co.*

*Latterly Consulting Engineer to the  
Traction Departments*

London

MACDONALD & EVANS, LTD.

8 JOHN STREET, BEDFORD ROW, W.C.1

1955

# CONTENTS

---

FOREWORD by F. WHYMAN, B.Sc.Tech., M.I.E.E.	v
PREFACE	vii
LIST OF ILLUSTRATIONS	xix
MOTIVE POWER, CHARACTERISTICS AND PERFORMANCES	1
1.1. Basis of speed-current-time performance curves.	
1.1.1. Acceleration—Fundamental considerations.	
1.1.2. Construction of the speed-time curve.	
1.2. Train performance.	
1.2.1. Examination of train performance.	
1.2.2. Energy consumption.	
1.2.3. Root-mean-square current per motor.	
1.2.4. Nearly constant watts per ton.	
1.2.5. Temperature rise of motors.	
1.2.6. Performance on level—a preliminary study.	
1.3. Speed-time curves on routes with gradients.	
1.4. Short-cut methods for speed-time curves.	
1.5. Effect of increasing the average speed on short runs.	
1.6. Factors influencing the average effective acceleration.	
1.6.1. Significance of absorption of tractive effort by rotary inertia.	
1.7. Traction service with multiple-unit trains, compared with locomotive-hauled trains.	
1.8. Method of determining the characteristic.	
VARIATION IN TRACTION MOTOR CHARACTERISTICS	35
2.1. Field control of motors.	
2.2. Stability of traction motors on fluctuating voltages.	
2.2.1. Armature-turns per pole.	
2.3. Motors with large range in field control.	
2.4. High-speed motors.	
FUNDAMENTAL FACTS CONCERNING MOTORS	47
3.1. Output coefficients of traction motors.	

- 3.2. Weight of traction motors.
- 3.3. Maximum safe speeds of armatures.
- 3.4. Points affecting motor design.
- 3.5. Motor gear ratios and gear-case clearances.

#### 4. BRAKING ON ELECTRIFIED RAILWAYS

64

- 4.1. Ordinary friction braking : General.
  - 4.1.1. Captain Galton's tests.
  - 4.1.2. Berlin-Zossen tests.
  - 4.1.3. Fall in coefficient of friction when braking on down-grades.
- 4.2. Retardation curves and equivalent straight-line braking.
  - 4.2.1. Plotting braking curves from the progressive coefficient of friction.
  - 4.2.2. Typical equivalent straight-line braking rates.
  - 4.2.3. Variable-pressure brakes.
  - 4.2.4. Brake-shoes other than cast iron.
  - 4.2.5. Freight trains braked by locomotive alone.
- 4.3. Electric braking : General.
- 4.4. Rheostatic braking with plain series connection of motor fields.
  - 4.4.1. Retarding effort deduced from motor characteristic.
  - 4.4.2. Limiting features in rheostatic braking.
  - 4.4.3. Practical grouping of motors and retardation/speed characteristics.
- 4.5. Rheostatic braking with separate excitation.
  - 4.5.1. Calculation of the braking characteristics.
  - 4.5.2. Suitable ohmic value of energy-absorbing resistor.
  - 4.5.3. Cast-iron resistors.
  - 4.5.4. Resistance chamber and ventilation.
  - 4.5.5. Forced draught ventilation for resistors.
- 4.6. Regenerative braking.
  - 4.6.1. Calculation of regeneration characteristic curves.
    - 4.6.1.1. Field excitation.
    - 4.6.1.2. Excitation when motoring in regenerative connections.
    - 4.6.1.3. Regenerated E.M.F.
    - 4.6.1.4. Tables of data for plotting the regenerative curves.
    - 4.6.1.5. Calculation of braking effort.
    - 4.6.1.6. Rearrangement of volts/r.p.m. data.
    - 4.6.1.7. Rearranged curves of volts/r.p.m. used for parallel motor combination.
    - 4.6.1.8. Limiting envelope of regenerative braking.
    - 4.6.1.9. Motoring in regenerative connections.
  - 4.6.2. Entry into regeneration.
  - 4.6.3. Exciter characteristics.
  - 4.6.4. Regeneration with six-motor equipment.
  - 4.6.5. Effect of line voltage variation on regeneration.
  - 4.6.6. Regeneration with axle-driven exciters.
    - 4.6.6.1. Calculation of axle-driven-exciter regeneration curves.

4.6.6.2. Use of an axle-driven exciter specially designed for the purpose.	
4.6.6.3. Compounding resistance.	
4.6.6.4. Method of calculating regeneration curves when using compounding resistance.	
4.6.7. Main features of regenerative braking.	
4.6.8. Power available on down-grades for regeneration.	
5. TRAIN RESISTANCE . . . . .	135
5.1. Mechanical resistance.	
5.2. Berlin-Zossen and St. Louis Exhibition tests.	
5.3. Air-resistance coefficients.	
5.3.1. Values of the coefficients.	
5.4. Effect of ground winds.	
5.4.1. Effect of gaps between coaches.	
5.5. Freight-train resistance.	
5.6. Additional causes of train resistance.	
5.6.1. Train resistance due to track curvature.	
5.7. Train resistance while coasting.	
6. PERMISSIBLE SPEEDS OF TRAINS ON CURVES . . . . .	160
7. ROTARY INERTIA IN ELECTRIC VEHICLES . . . . .	165
7.1. Example of rotary inertia for multiple-unit train.	
7.2. Tables of masses equivalent to rotary inertia.	
8. WEIGHT TRANSFERENCE . . . . .	171
8.1. Weight transference of a four-axle locomotive.	
8.2. Improving weight transference conditions.	
8.2.1. Improvement by altering motor positions.	
8.3. Improving weight transference with six-axled locomotives.	
8.4. Normal motor-coach weight transference.	
8.5. Frame-mounted motors with quill or equivalent drive.	
9. ADHESION BETWEEN TYRES AND RAILS . . . . .	185
9.1. Starting notches for acceleration.	
9.2. A handy chart for fixing the ratio of locomotive to train weight.	
10. ENERGY CONSUMPTION OF AUXILIARY SERVICES . . . . .	193
11. AUXILIARY MACHINES FOR LOCOMOTIVES AND MOTOR-COACHES . . . . .	197
11.1. Motor-generators.	
11.2. Compressors.	

- 11.3. Vacuum pumps—Exhausters.
- 11.4. Electrically fired boilers for steam heating of trains.
- 11.5. Blower fans and forced ventilation of equipment.
  - 11.5.1. Relation between pressure, velocity and power, etc.
  - 11.5.2. Losses in duct systems.
  - 11.5.3. Water gauge pressure at motors.
  - 11.5.4. Effect of high altitudes.
  - 11.5.5. Design of duct system.
  - 11.5.6. Testing the air flow in the ducts.
  - 11.5.7. Centrifugal blower fan characteristics.
  - 11.5.8. Ventilation of resistances.
- 12. GRAPHIC TIME-TABLES AND POWER DEMAND . 214
  - 12.1. Average power demand.
  - 12.2. Power loading curves.
  - 12.3. Sharing of loads between substations and voltage drops.
  - 12.4. The case for several substations.
  - 12.5. Losses in current conductor system.
  - 12.6. Conditions determining the position of substations.
- 13. TRANSMISSION TO MERCURY-ARC SUBSTATIONS 230
  - 13.1. Six-phase rectifiers operating on 50-period three-phase supply.
    - 13.1.1. Duplication of the railway transmission lines.
    - 13.1.2. Star and delta primary winding.
    - 13.1.3. Double-star secondary with interphase transformer.
    - 13.1.4. Delta/double-star with interphase transformer.
    - 13.1.5. Star and delta primaries to double star and interphase transformer.
    - 13.1.6. Three-core cable transmission lines.
  - 13.2. Sine-wave transmission of power.
  - 13.3. Resistance and reactance of transmission wires.
  - 13.4. Resistance of running rails and collector rails.
- 14. SELF-CONTAINED POWER UNITS WITH ELECTRIC TRANSMISSION . . . . . 245
  - 14.1. Generator characteristics for constant power input.
  - 14.2. Motor characteristic and final-power characteristic.
  - 14.3. Diesel-engine horse-power ratings.
  - 14.4. Comparison of characteristics of constant power and ordinary traction systems.
  - 14.5. Self-contained power units used for suburban services.
  - 14.6. Weight of self-contained power units.
  - 14.7. Investigation of main-line services.
    - 14.7.1. Service obtained with 3.5-h.p./ton at the generator coupling.
    - 14.7.2. Time lost in accelerating and braking.

- 14.8. Variations in specific weight of diesel-electric locomotives.
- 14.9. Gas-turbo-electric locomotives.
- 14.10. Rating of electric transmission for diesel-electric and gas-turbo-electric locomotives.
  
- 15. COMPARISON BETWEEN SELF-CONTAINED POWER UNITS AND STRAIGHT-ELECTRIC TRACTION SYSTEMS . . . . . 280
  - 15.1. Comparison of diesel-electric and straight-electric traction.
    - 15.1.1. Economic balance.
    - 15.1.2. Comparison of horse-powers of diesel-electric and electric locomotives.
    - 15.1.3. Weight factors affecting relative ton-miles and total horse-power of locomotives.
    - 15.1.4. Capital cost of locomotives.
    - 15.1.5. Capital cost of fixed installations.
    - 15.1.6. Fuel and electric energy costs.
    - 15.1.7. Work done at the wheels.
    - 15.1.8. Maintenance of locomotives and fixed installations.
    - 15.1.9. Example of calculation of economic balance with respect to horse-power per ton.
    - 15.1.10. Conclusions and observations from calculations.
    - 15.1.11. Application to a specific traction problem.
  
- 16. COMPARISON BETWEEN DIESEL-ELECTRIC AND GAS-TURBO-ELECTRIC LOCOMOTIVE OPERATION . . . . . 301
  - 16.1. Capital cost of gas-turbo-electric locomotives.
  - 16.2. Relative cost of maintenance.
  - 16.3. Sinking fund.
  - 16.4. Interest on capital.
  - 16.5. Fuel consumption.
  - 16.6. Lubricating oil.
  - 16.7. Comparison between rival locomotives cost per year.
  - 16.8. Comparison between G.T.E. and straight-electric locomotive operation.
  
- 17. COMPARISON BETWEEN DIFFERENT SYSTEMS OF ELECTRIC TRACTION . . . . . 315
  - 17.1. Capital cost of locomotives.
  - 17.2. Locomotive maintenance.
  - 17.3. Electric energy consumption.
  - 17.4. Weight factors.
  - 17.5. Data for comparison between systems.

- 17.6. Comparison between 1500-volt and 3000-volt d.c. systems.
  - 17.7. Comparison between 3000-volt d.c. and 15 000-volt single-phase a.c. systems.
18. EXAMPLE OF RAILWAY ELECTRIFICATION 322
- 18.1. Loads to be hauled.
  - 18.2. Speeds.
  - 18.3. Resistance to traction.
  - 18.4. Locomotive weight and type.
  - 18.5. Locomotive characteristics.
  - 18.6. The motor design.
  - 18.7. System voltage.
  - 18.8. Freight and passenger train power demands.
  - 18.9. Performance of trains over the electrified route.
  - 18.10. Adhesive weight of the locomotive.
  - 18.11. Performance of trains.
  - 18.12. Time-temperature curves.
  - 18.13. Schedule speeds.
  - 18.14. Graphic time-table for daily service.
  - 18.15. Ton-mileage.
  - 18.16. System of electrification.
  - 18.17. Number of locomotives required.
  - 18.18. Overhead conductor system for 3000 volts d.c. system.
  - 18.19. Spacing of substations.
  - 18.20. General load conditions.
  - 18.21. Losses between supply source and the trains.
  - 18.22. Number of substations required and their capacity.
  - 18.23. Transmission lines to substations.
    - 18.23.1. Other conditions of supply.
19. MECHANICAL PARTS OF ELECTRIC LOCOMOTIVES 370
- 19.1. Freight locomotives.
  - 19.2. Locomotives for high-speed running.
  - 19.3. Some of the causes of bad riding and their cure or amelioration.
  - 19.4. Points to be observed in order to improve the running of electric locomotives.
  - 19.5. Link-sprung non-bolster body suspension.
  - 19.6. Axle loading.

CONTENTS

xvii

20. TRACTION CONTROL . . . . .	383
20.1. Starting notches.	
20.1.1. Notching curves for motors with saturated characteristics.	
20.2. Field control of motors.	
20.3. Ventilation of resistors.	
20.4. Starting of auxiliary machines.	
20.5. Electrical devices connected with braking.	
20.6. Layout of apparatus.	
APPENDICES . . . . .	396
1. Conductor-rail systems.	
2. Notes on six-phase rectification, by F. Whyman.	
3. Some useful constants and formulæ.	
BIBLIOGRAPHY . . . . .	405
INDEX . . . . .	407
SUPPLIERS OF ELECTRIC TRACTION EQUIPMENT . . . . .	417